



Cambridge International AS & A Level

PHYSICS

9702/42

Paper 4 A Level Structured Questions

October/November 2021

MARK SCHEME

Maximum Mark: 100

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2021 series for most Cambridge IGCSE™, Cambridge International A and AS Level components and some Cambridge O Level components.

This document consists of **19** printed pages.

Abbreviations

/	Alternative and acceptable answers for the same marking point.
()	Bracketed content indicates words which do not need to be explicitly seen to gain credit but which indicate the context for an answer. The context does not need to be seen but if a context is given that is incorrect then the mark should not be awarded.
—	Underlined content must be present in answer to award the mark. This means either the exact word or another word that has the same technical meaning.

Mark categories

B marks	These are <u>independent</u> marks, which do not depend on other marks. For a B mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer.
M marks	These are <u>method</u> marks upon which A marks later depend. For an M mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer. If a candidate is not awarded an M mark, then the later A mark cannot be awarded either.
C marks	These are <u>compensatory</u> marks which can be awarded even if the points to which they refer are not written down by the candidate, providing subsequent working gives evidence that they must have known them. For example, if an equation carries a C mark and the candidate does not write down the actual equation but does correct working which shows the candidate knew the equation, then the C mark is awarded. If a correct answer is given to a numerical question, all of the preceding C marks are awarded automatically. It is only necessary to consider each of the C marks in turn when the numerical answer is not correct.
A marks	These are <u>answer</u> marks. They may depend on an M mark or allow a C mark to be awarded by implication.

Annotations

✓	Indicates the point at which a mark has been awarded.
X	Indicates an incorrect answer or a point at which a decision is made not to award a mark.
XP	Indicates a physically incorrect equation ('incorrect physics'). No credit is given for substitution, or subsequent arithmetic, in a physically incorrect equation.

PUBLISHED

ECF	Indicates 'error carried forward'. Answers to later numerical questions can always be awarded up to full credit provided they are consistent with earlier incorrect answers. <u>Within</u> a section of a numerical question, ECF can be given after AE, TE and POT errors, but not after XP.
AE	Indicates an arithmetic error. Do not allow the mark where the error occurs. Then follow through the working/calculation giving full subsequent ECF if there are no further errors.
POT	Indicates a power of ten error. Do not allow the mark where the error occurs. Then follow through the working/calculation giving full subsequent ECF if there are no further errors.
TE	Indicates incorrect transcription of the correct data from the question, a graph, data sheet or a previous answer. For example, the value of 1.6×10^{-19} has been written down as 6.1×10^{-19} or 1.6×10^{19} . Do not allow the mark where the error occurs. Then follow through the working/calculation giving full subsequent ECF if there are no further errors.
SF	Indicates that the correct answer is seen in the working but the final answer is incorrect as it is expressed to too few significant figures.
BOD	Indicates that a mark is awarded where the candidate provides an answer that is not totally satisfactory, but the examiner feels that sufficient work has been done ('benefit of doubt').
CON	Indicates that a response is contradictory.
I	Indicates parts of a response that have been seen but disregarded as irrelevant.
M0	Indicates where an A category mark has not been awarded due to the M category mark upon which it depends not having previously been awarded.
^	Indicates where more is needed for a mark to be awarded (what is written is not wrong, but not enough). May also be used to annotate a response space that has been left completely blank.
SEEN	Indicates that a page has been seen.

PUBLISHED

Question	Answer	Marks
1(a)	acceleration perpendicular to velocity	B1
1(b)(i)	decreases	B1
1(b)(ii)	(acceleration of) 9.8 m s^{-2} is caused by weight of car or centripetal force must be greater than weight of car	B1
	(acceleration $> 9.8 \text{ m s}^{-2}$) requires contact <u>force</u> from track or (centripetal force $>$ weight) requires contact <u>force</u> from track	B1
1(c)	$\frac{1}{2}mv_Y^2 = \frac{1}{2}mv_X^2 - mgh$	C1
	$a = v^2 / r$	C1
	$v_Y^2 = 3.8^2 - 2 \times 9.81 \times 0.62$ so $v_Y = 1.5 \text{ m s}^{-1}$ $a = 1.5^2 / 0.31 = 7.3 \text{ m s}^{-2}$ (which is less than 9.8 m s^{-2}) so no	A1
	or	
	$v_Y = \sqrt{(9.81 \times 0.31)} = 1.74 \text{ m s}^{-1}$ so $v_X^2 = 1.74^2 + 2 \times 9.81 \times 0.62$ $v_X = 3.9 \text{ m s}^{-1}$ (which is greater than 3.8 m s^{-1}) so no	(A1)
1(d)	acceleration is independent of mass so makes no difference or mass cancels in the equation so makes no difference	B1

PUBLISHED

Question	Answer	Marks
2(a)	(gravitational) field strength equals (gravitational) potential gradient	M1
	reference to minus sign	A1
2(b)(i)	potential is zero at infinity	B1
	(gravitational) force is attractive	B1
	(test) mass getting closer (from infinity) loses potential energy	B1
2(b)(ii)	<ul style="list-style-type: none"> potential at (surface of) planet is smaller than at (surface of) moon potential gradient at (surface of) planet is smaller than at (surface of) moon magnitude of potential varies inversely with distance from centre near the spheres (point of) maximum potential is nearer to moon than planet <i>Any two points, 1 mark each</i>	B2
2(b)(iii)	sketch: one curve, starting with gradient of decreasing magnitude at $2R$ and finishing with gradient of increasing magnitude at $D - R$	B1
	field strength shown as zero (only) near the point of maximum potential	B1
	negative field strength near one sphere and positive field strength near the other	B1

PUBLISHED

Question	Answer	Marks
3(a)(i)	no loss of <u>kinetic</u> energy	B1
3(a)(ii)	<ul style="list-style-type: none"> • <u>molecules</u> have negligible volume (compared with gas/container) • no forces between <u>molecules</u> (except during collisions) • <u>molecules</u> are in random motion • collisions are instantaneous <i>Any two points, 1 mark each</i>	B2
3(b)(i)	$2mu$	A1
3(b)(ii)	$2L / u$	A1
3(b)(iii)	force = change in momentum / time = $2mu / (2L / u)$ $= mu^2 / L$	A1
3(b)(iv)	pressure = force / area = $(mu^2 / L) / L^2$ $= mu^2 / L^3$	A1
3(c)	$pV = NkT$	C1
	$NkT = \frac{1}{3}Nm\langle c^2 \rangle$ leading to $\frac{1}{2}m\langle c^2 \rangle = (3/2)kT$ <u>and</u> $\frac{1}{2}m\langle c^2 \rangle = E_K$	A1
3(d)	$\frac{1}{2} \times 3.34 \times 10^{-27} \times \langle c^2 \rangle = (3/2) \times 1.38 \times 10^{-23} \times (25 + 273)$	C1
	r.m.s. speed = $1.9 \times 10^3 \text{ m s}^{-1}$	A1

PUBLISHED

Question	Answer	Marks
4(a)	straight line through the origin	B1
	negative gradient	B1
4(b)	$a = (-)\omega^2 x$ and $T = 2\pi / \omega$	C1
	e.g. $\omega = \sqrt{(0.80 / 0.12)}$ (<i>any correct pair of values of a and x</i>) (= 2.58 rad s ⁻¹)	C1
	$T = 2\pi / 2.58$ = 2.4 s	A1
4(c)(i)	Point labelled P at one end of the line	B1
4(c)(ii)	Point labelled Q at displacement with magnitude more than half but less than maximum	B1

PUBLISHED

Question	Answer	Marks
5(a)(i)	unmodulated (radio) waves would interfere with each other or not modulating would require aerials too long (to be practical)	B1
5(a)(ii)	advantage: <ul style="list-style-type: none"> • can transmit higher frequencies • higher quality <u>reproduction</u> • less prone to interference • same frequency can be used in different areas (any one point)	B1
	disadvantage: <ul style="list-style-type: none"> • takes up greater bandwidth • shorter range of transmission • requires a greater number of transmitting aerials (any one point)	B1
5(b)	AM amplitude: min. 8 mV and max. 12 mV	B1
	AM frequency: min. 100 kHz and max. 100 kHz	B1
	FM amplitude: min. 10 mV and max. 10 mV	B1
	FM frequency: min. 90 kHz and max. 110 kHz	B1
5(c)	8.4 kHz	A1

PUBLISHED

Question	Answer	Marks
6(a)	work done per unit charge	B1
	(work done in) moving positive charge from infinity	B1
6(b)	$C = Q / V$	C1
	$V = Q / (4\pi\epsilon_0 r)$ and so $C = Q / [Q / (4\pi\epsilon_0 r)] = 4\pi\epsilon_0 r$	A1
6(c)	$Q = 4\pi\epsilon_0 r V = 4\pi \times 8.85 \times 10^{-12} \times 0.13 \times 4500$ $(= 6.5 \times 10^{-8} \text{ C})$	C1
	$(Q - q) / 13 = q / 5.2$	C1
	$5.2Q - 5.2q = 13q$, so $q = (5.2 / 18.2)Q$ $q = (5.2 / 18.2) \times 6.5 \times 10^{-8}$ $= 1.9 \times 10^{-8} \text{ C}$	A1
	or	
	$V_T = Q_T / C_T$ $= 6.5 \times 10^{-8} / [4\pi \times 8.85 \times 10^{-12} \times (0.13 + 0.052)]$ $(= 3210 \text{ V})$	(C1)
	$q = 4\pi \times 8.85 \times 10^{-12} \times 0.052 \times 3210$ $= 1.9 \times 10^{-8} \text{ C}$	(A1)

PUBLISHED

Question	Answer	Marks
7(a)	output voltage / input voltage	M1
	input (voltage) is difference between (inverting and non-inverting) inputs	A1
7(b)	<ul style="list-style-type: none"> • reduces the gain • greater bandwidth • more stable <i>Any two points, 1 mark each</i>	B2
7(c)(i)	inverting amplifier	B1
7(c)(ii)	X marked anywhere between right-hand edge of $480\ \Omega$ resistor, left-hand edge of $1.2\ \text{k}\Omega$ resistor and the inverting input	B1
7(c)(iii)	gain = $(-R_f / R_i)$	C1
	= $(-1200 / 480)$	A1
	= -2.5	
7(c)(iv)	$V_{\text{IN}} = 6.5 / (-2.5)$ $= -2.6\ \text{V}$	A1
7(c)(v)	$(-2.5) \times (-5.4) = +13.5\ \text{V}$, and so output saturates $V_{\text{OUT}} = (+)8.0\ \text{V}$	A1

PUBLISHED

Question	Answer	Marks
8(a)(i)	arrow from Q pointing downwards, labelled B	B1
8(a)(ii)	arrow from Q pointing towards P, labelled F	B1
8(b)(i)	force is proportional to product of both currents (I and $2I$) or Newton's third law	B1
	forces are equal	B1
8(b)(ii)	opposite	B1

Question	Answer	Marks
9(a)(i)	emission of electrons (from a metal surface)	B1
	when electromagnetic radiation is incident (on electrons)	B1
9a(ii)	<u>minimum</u> energy required for an electron to leave surface	B1
9(b)(i)	threshold (frequency)	B1
9(b)(ii)	<ul style="list-style-type: none"> photons are (discrete) packets of energy energy of photons depends on frequency (of EM radiation) electrons can only absorb a single photon (of energy) <i>Any two points, 1 mark each</i>	B2
	emission only possible if photon energy is at least the work function	B1
9(b)(iii)	work function = $hf_0 = 6.63 \times 10^{-34} \times 6.93 \times 10^{14}$	C1
	$= 4.59 \times 10^{-19} \text{ (J)}$ $= 4.59 \times 10^{-19} / 1.60 \times 10^{-19} \text{ (eV)}$ $= 2.87 \text{ eV}$	A1

PUBLISHED

Question	Answer	Marks
10(a)(i)	to increase the magnetic flux linkage (between the coils)	B1
10(a)(ii)	to reduce energy losses	B1
	by reducing induced currents	B1
10(b)(i)	maximum $V_{\text{OUT}} = 12\,000 \times (625 / 25\,000)$ $= 300\text{ V}$	A1
10(b)(ii)	r.m.s. current $= 300 / (640 \times \sqrt{2})$ $= 0.33\text{ A}$	A1
10(b)(iii)	sketch: sinusoidal shape in positive half of the graph, sitting with 'minima' resting on the time-axis (at $P = 0$)	B1
	each 'cycle' shown repeating every 20 ms	B1
	maximum P shown as 140 W	B1
10(c)	power curve is symmetrical about the midpoint (on the power axis)	B1
	mean power is half the peak power	B1

PUBLISHED

Question	Answer	Marks
11(a)	generates <u>ultrasound</u>	B1
	detects <u>reflected</u> ultrasound	B1
	applied p.d. causes crystal to vibrate or vibrations cause crystal to generate an e.m.f.	B1
11(b)(i)	product of density and speed	M1
	speed of ultrasound in medium	A1
11(b)(ii)	difference between (the specific acoustic impedances)	C1
	<ul style="list-style-type: none"> • if similar/same then reflection coefficient is zero/very low • if very different then reflection coefficient is (nearly) 1 • the lower the difference means lower the reflection coefficient <i>(any one point)</i>	A1

PUBLISHED

Question	Answer	Marks
12(a)(i)	cannot predict when a particular nucleus will decay or cannot predict which nucleus will decay next	B1
12(a)(ii)	(decay is) not affected by external (environmental) factors	B1
12(b)(i)	$A = A_0 \exp(-\lambda t)$ and so $\ln A = \ln A_0 - \lambda t$ gradient of line = $(-)\lambda$	C1
	$\lambda = (36.4 - 35.0) / (20 - 0)$ (= 0.07(0) min ⁻¹)	C1
	half-life = $\ln 2 / \lambda$ = $\ln 2 / 0.070$ = 10 min	A1
	or	
	$A_0 = \exp(-36.4) = 6.43 \times 10^{15}$ (Bq)	(C1)
	$A_0 / 2 = 3.21 \times 10^{15}$ (Bq), so $\ln(A_0 / 2) = 35.7$	(C1)
	read off half-life = 10 min	(A1)
	or	
	(at one half-life,) $\ln A = 36.4 - \ln 2$	(C1)
	= 35.7	(C1)
	read off half-life = 10 min	(A1)

PUBLISHED

Question	Answer	Marks
12(b)(ii)	$A = \lambda N$	C1
	$N = \text{mass} / (\text{nucleon number} \times u)$ or $N = (\text{mass} / \text{nucleon number}) \times N_A$	C1
	$\exp(36.4) = (1.17 \times 10^{-3} \times 5.66 \times 10^{-7}) / (\text{nucleon number} \times 1.66 \times 10^{-27})$ or $\exp(36.4) = (1.17 \times 10^{-3} \times 5.66 \times 10^{-4} \times 6.02 \times 10^{23}) / \text{nucleon number}$ nucleon number = 62	A1