



# Cambridge International AS & A Level

---

## PHYSICS

9702/23

Paper 2 AS Level Structured Questions

May/June 2023

MARK SCHEME

Maximum Mark: 60

---

**Published**

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2023 series for most Cambridge IGCSE, Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

**6** Calculation specific guidance

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g.  $a \times 10^n$ ) in which the convention of restricting the value of the coefficient ( $a$ ) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

**7** Guidance for chemical equations

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

**Abbreviations**

/	Alternative and acceptable answers for the same marking point.
( )	Bracketed content indicates words which do not need to be explicitly seen to gain credit but which indicate the <b>context</b> for an answer. The context does not need to be seen but if a context is given that is incorrect then the mark should not be awarded.
—	Underlined content must be present in answer to award the mark. This means either the exact word or another word that has the same technical meaning.

**Mark categories**

<b>B</b> marks	These are <u>independent</u> marks, which do not depend on other marks. For a <b>B</b> mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer.
<b>M</b> marks	These are <u>method</u> marks upon which <b>A</b> marks later depend. For an <b>M</b> mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer. If a candidate is not awarded an <b>M</b> mark, then the later <b>A</b> mark cannot be awarded either.
<b>C</b> marks	<p>These are <u>compensatory</u> marks which can be awarded even if the points to which they refer are not written down by the candidate, providing subsequent working gives evidence that they must have known them. For example, if an equation carries a <b>C</b> mark and the candidate does not write down the actual equation but does correct working which shows the candidate knew the equation, then the <b>C</b> mark is awarded.</p> <p>If a correct answer is given to a numerical question, all of the preceding <b>C</b> marks are awarded automatically. It is only necessary to consider each of the <b>C</b> marks in turn when the numerical answer is not correct.</p>
<b>A</b> marks	These are <u>answer</u> marks. They may depend on an <b>M</b> mark or allow a <b>C</b> mark to be awarded by implication.

**PUBLISHED**

Question	Answer	Marks
1(a)	$t = \sqrt{2s / g}$ $= \sqrt{[(2 \times 36) / 9.81]}$	<b>C1</b>
	$= 2.7 \text{ s}$	<b>A1</b>
1(b)	<ul style="list-style-type: none"> <li>• reaction time between hearing the splash and stopping the stop-watch</li> <li>• the sound (of the splash) takes time to reach the student <b>or</b> the stone hits the water at a different time to the sound being heard <b>or</b> the sound (of the splash) has to travel to the student</li> <li>• the student might not let go of the stone from ground level</li> <li>• the student might not let go of the stone and start the stop-watch at the same time</li> <li>• stop-watch may not be properly calibrated / has a zero error</li> <li>• (local value of) <math>g</math> is not (exactly) <math>9.81 \text{ (m s}^{-2}\text{)}</math></li> <li>• stone given initial velocity / initial velocity not zero</li> <li>• stone does not fall (exactly) vertically / in a straight line</li> </ul> <p><i>Any three points, 1 mark each</i></p>	<b>B3</b>
1(c)	precise: results are close together / have little scatter	<b>B1</b>
	not accurate: the values are not close to / 50% different / (very) different from the true value	<b>B1</b>

**PUBLISHED**

Question	Answer	Marks
2(a)	$F = 1050 \times 9.81 \times 0.21V$ <b>or</b> $W = \rho \times 9.81 \times V$	<b>C1</b>
	$0.21V \times 1050 (\times 9.81) = V (\times 9.81) \times \rho$	<b>A1</b>
	$\rho = 220 \text{ kg m}^{-3}$	
2(b)(i)	$F = 1050 \times 9.81 \times V$ <b>or</b> $W = 220 \times 9.81 \times V$	<b>C1</b>
	$(V \times 1050 \times 9.81) - (V \times 220 \times 9.81) = (V \times 220) \times a$	<b>C1</b>
	$a = 37 \text{ m s}^{-2}$	<b>A1</b>
2(b)(ii)	the (downward) drag / viscous force increases (with speed)	<b>M1</b>
	resultant force decreases (as upthrust and weight remain the same)	<b>M1</b>
	acceleration decreases (as its velocity increases)	<b>A1</b>

**PUBLISHED**

Question	Answer	Marks
3(a)	<u>sum</u> / <u>total</u> momentum before = <u>sum</u> / <u>total</u> momentum after <b>or</b> <u>sum</u> / <u>total</u> momentum (of a system of objects) is constant	<b>M1</b>
	if no (resultant) external force / for an isolated system	<b>A1</b>
3(b)(i)	$3m \times 4 = m \times v \sin \theta$  ( $v \sin \theta = 12$ )	<b>C1</b>
	$2m \times 6 = m \times v \cos \theta$  ( $v \cos \theta = 12$ )	<b>C1</b>
	therefore $\sin \theta = \cos \theta$ <b>or</b> $\tan \theta = 1$  $\theta = 45^\circ$	<b>A1</b>
3(b)(ii)	$mv \times \cos 45^\circ = 12m$ <b>or</b> $mv \times \sin 45^\circ = 12m$ <b>or</b> $(mv)^2 = (3m \times 4)^2 + (2m \times 6)^2$	<b>C1</b>
	$v = 17 \text{ m s}^{-1}$	<b>A1</b>
3(c)(i)	(chemical energy) = $0.0050 \times 700 = 3.5 \text{ (J)}$ <b>or</b> (chemical energy) = $5.0 \times 0.700 = 3.5 \text{ (J)}$	<b>A1</b>

**PUBLISHED**

Question	Answer	Marks
3(c)(ii)	$E = \frac{1}{2}mv^2$	<b>C1</b>
	total $E = (0.5 \times 3m \times 4^2) + (0.5 \times 2m \times 6^2) + (0.5 \times m \times 17^2)$	<b>C1</b>
	$3.5 = 204m$	<b>A1</b>
	$m = 0.017 \text{ kg}$	

Question	Answer	Marks
4(a)	the number of wavefronts/crests/troughs passing a fixed point per unit time <b>or</b> the number of oscillations per unit time (of source / point on wave / particle of medium)	<b>B1</b>
4(b)(i)	$T = 4 \times 0.50 \times 10^{-3}$	<b>C1</b>
	$(= 2.0 \times 10^{-3} \text{ s})$	
	$f = 1 / 2.0 \times 10^{-3}$ $= 500 \text{ Hz}$	<b>A1</b>
4(b)(ii)	amplitude $= 2.8 \times 0.20$ $= 0.56 \text{ V}$	<b>A1</b>
4(c)	period same as original trace	<b>B1</b>
	sinusoidal wave of constant amplitude less than 2.8 cm throughout	<b>M1</b>
	amplitude 1.4 cm	<b>A1</b>

**PUBLISHED**

Question	Answer	Marks
4(d)(i)	when (two or more) waves <u>meet</u> (at a point)	<b>B1</b>
	(resultant) displacement is the sum of the individual displacements	<b>B1</b>
4(d)(ii)	node-to-node separation is $\lambda / 2$ <b>or</b> microphone moves through 3 node-to-node separations <b>or</b> $d = 1.5\lambda$	<b>C1</b>
	$\lambda = 1.05 / 1.5$  $= 0.70 \text{ m}$	<b>A1</b>
4(d)(iii)	$v = f \times \lambda$	<b>C1</b>
	$= 500 \times 0.70$  $= 350 \text{ m s}^{-1}$	<b>A1</b>



**PUBLISHED**

Question	Answer	Marks
5(a)	correct symbol for the heater <b>or</b> for the LDR	<b>M1</b>
	all correct symbols in series (ignore voltmeter) and no extra symbols	<b>A1</b>
	correct symbol for voltmeter and in parallel with the heater	<b>B1</b>
5(b)(i)	$R = \rho L / A$	<b>C1</b>
	$= (1.1 \times 10^{-6} \times 2.0) / 3.8 \times 10^{-7}$	<b>A1</b>
	$= 5.8 \Omega$	
5(b)(ii)	$I = 4.8 / 5.8$	<b>A1</b>
	$= 0.83 \text{ A}$	
5(c)(i)	A larger (for new wire) <b>or</b> $A \propto d^2$ (and $d$ larger for new wire) <b>or</b> $R \propto 1 / d^2$ (and $d$ larger for new wire)	<b>M1</b>
	so $R$ is less (than that of first wire)	<b>A1</b>
5(c)(ii)	(heater / total resistance decreases so) current (in circuit) increases (so p.d. across LDR increases) <b>or</b> heater resistance decreases so it has a smaller share/proportion/fraction of the (total) voltage / e.m.f.	<b>M1</b>
	(so voltmeter) reading is less (than 4.8 V)	<b>A1</b>

**PUBLISHED**

Question	Answer	Marks
6(a)	(Young modulus =) stress / strain	<b>B1</b>
6(b)(i)	unstretched length = 1.9980 m	<b>A1</b>
6(b)(ii)	stress = $F / A$	<b>C1</b>
	$= 30 / 9.5 \times 10^{-7}$ $= 3.2 \times 10^7 \text{ Pa}$	<b>A1</b>
	strain = $0.0050 / 1.9980$ $= 2.5 \times 10^{-3}$	<b>A1</b>

Question	Answer	Marks
7(a)	down charge = $-1/3(e)$ <b>and</b> charm charge = $(+)2/3(e)$	<b>B1</b>
	all antiquarks have opposite sign and same (non-zero) magnitude of charge as the corresponding quarks	<b>B1</b>
7(b)(i)	udd <b>or</b> cdd	<b>B1</b>
7(b)(ii)	$u\bar{d}$ <b>or</b> $c\bar{d}$	<b>B1</b>
7(c)(i)	lepton(s)	<b>B1</b>
7(c)(ii)	positron / neutrino / antineutrino	<b>B1</b>